



T800-Ex RUGGED

- 8.1" HD LumiBond® 2.0 display for better viewing experience
- Getac proprietary SnapBack add-on featuring Smart card and contactless RFID reader Combo or 2nd expanded battery
- Choice of 1D/2D imager barcode reader, Serial port, Micro SD or Ethernet
- Up to 10 hours of battery life with one charge. LifeSupport™ battery swappable technology for uninterrupted battery life
- MIL-STD-810G and IP65 certified
- Enhanced Enterprise Security with optional Intel vPro, Windows Disk Encryption, TPM 2.0 and many more multi-factor authentication options.













SnapBack add-on



Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Platform Options:

Intel® Atom Processor x7-Z8750 1.6 GHz, burst up to 2.56 GHz - 2MB Cache

VGA Controller

Intel® HD Graphics

Display

8.1" IPS TFT LCD HD (1280 x 800) 600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory

4GB LPDDR3 expandable to 8GB Optional eMMC 64GB / 128GB

6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)

Pointing Device

Touchscreen

- Capacitive multi-touch screen Optional dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional 1D/2D imager barcode reader

I/O Interface

FHD webcam x 1 8M pixels auto focus rear camera x 1 USB 3.0 (9-pin) x 1 Headphone out/Mic-in Combo x 1 DC in Jack x 1 Micro HDMI x 1

Communication Interface

Intel® Dual Band Wireless-AC 7265, 802.11ac Bluetooth (v4.0) Optional dedicated GPS Optional 4G LTE mobile broadband

Security Feature

TPM 2.0

AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-lon battery (7.4V, 4200mAh)

Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94") 0.91kg (2 lbs)ii

Rugged Feature

MIL-STD-810G certified and IP65 certified 6 feet drop resistant Vibration & drop resistant

Environmental Specification

Temperature iii.

- Operating: -21°C to 50°C / -5.8°F to 122°F Storage: -51°C to 71°C / -60°F to 160°F
- Humidity: 95% RH , non-condensing

ATEX / IECEx zone 2/22 II 3G Ex ic IIC T4 Gc II 3D Ex ic IIIB T130°C Dc

Getac Utility (including Power Manager) Getac Geolocation Getac Barcode Manager Adobe® Reader® Optional Absolute DDS® Persistence Accessories

Main battery (7.4V, 4200mAh) 2nd expanded battery (14.4V, 2100 mAh) AC adapter (65W, 100-240VAC) Capacitive stylus (Hard-tip) Digitizer pen

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings. Weight and dimensions vary from configurations and optional accessories. Tested by a national independent third party test lab following MIL-STD-810G.

T800-Ex Fully Rugged **Tablet**



Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2018 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request. V01M09Y18WW

TEMPEL GROUP



Calle Cobalto 4, 08907 Hospitalet de Llobregat, España www.tempelgroup.com info@tempelgroup.com