Getac



ZX70-EX FULLY RUGGED TABLET

- 7" LumiBond® Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- ATEX & IECEx Explosive Atmosphere Certified
- 6 Feet Drop , MIL-STD-810G and IP67 Certified
- Optional Barcode Reader and HF RFID
- Optional 4G LTE WWAN













Specifications

Operating System

Android 6.0

Mobile Computing Platform

Intel Atom® Processor x5-Z8350 1.44GHz, burst up to 1.92 GHz - 2MB cache

VGA Controller

Intel® HD Graphics

Display

7" IPS TFT LCD HD (1280 x 720) LumiBond® display with Getac sunlight readable technology Capacitive touchscreen with glove on

Storage & Memory

2GB LPDDR3 expandable to 4GB Optional eMMC 32GB / 64GB / 128GB

Keyboard

4 tablet buttons (Power, Barcode Launch Button, Volume Up, Volume Down)

Pointing Device

Touchscreen

- Capacitive multi-touch screen

Expansion Slot

MicroSD x1

I/O Interface

FHD webcam x 1 8M pixels auto focus rear camera x 1 MicroUSB 2.0 (Client) x 1 USB 2.0 (Host) x 1 DC in Jack x 1

Communication Interface

Wi-Fi 802.11n Bluetooth (v4.0) Dedicated GPS

Optional 4G LTE mobile broadband

Security Feature

Optional Contactless HF RFID/NFC combo reader^{ii,iii} Optional Barcode reader

AC adapter (24W, 100-240VAC, 50 / 60Hz) Li-lon battery (3.8V, 8400mAh)

Dimension (W x D x H) & Weight

218 x 142 x 27 mm (8.58 " x 5.6" x 1.08") 780g (1.71lbs)^v

Rugged Feature MIL-STD-810G certified and IP67 certified MIL-31D-810G certified and IP67 certified
6 feet drop resistant
Vibration & drop resistant
e-Mark certified for vehicle usage
ATEX & IECEx Explosive Atmosphere Certified

Environmental Specification

Temperature^v:

- Operating: -21°C to 60°C / -6°F to 140°F Storage: -40°C to 71°C / -40°F to 160°F
- Humidity:
 95% RH , non-condensing
 ATEX / IECEx zone 2/22
 II 3G Ex ic IIC T5 Gc II 3D Ex ic IIIB T100°C Dc

Getac Settings, Google Chrome, Gmail, Google+, Google Maps, Google Play Music, Google Play Movies, Google Play Books, Google Play Newsstand, Google Play Games, Google Drive, YouTube, Google Plus Photos, Hangouts

AC adapter (24W; 12V/2A, 100-240VAC; 50 / 60 Hz) Capacitive stylus Hand strap with Stylus Holder Wrist strap

Anti-static protection film

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

3 years Bumper-to-Bumper

- i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area. 13.56MHz Contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™
- compliant).
 HF RFID/NFC combo reader applies to US & EU
 Weight varies from configurations and
- optional accessories.
 Tested by a national independent third party
- test lab following MIL-STD-810G.

ZX70-Ex Fully Rugged **Tablet**



Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com | www.getac.com



Copyright © 2018 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request. V01M09Y18WW

TEMPEL GROUP



Calle Cobalto 4, 08907 Hospitalet de Llobregat, España www.tempelgroup.com info@tempelgroup.com